

# Itona TC3531-LI



## Powered by Gio Linux Embedded



The Itona TC3531-LI is powered by the Gio Linux Embedded operating system.

The Itona TC3531-LI boasts a very rich application set featuring X-Windows Server, ICA, RDP and UNIX Connectivity Clients, allowing swift connection to UNIX and IBM mainframes together with Microsoft servers.

Features & Benefits	Specifications	
<p><b>Features</b></p> <ul style="list-style-type: none"> <li>❖ VIA C3 EBGA Processor</li> <li>❖ 32MB IDE Flash</li> <li>❖ 64MB RAM (DIMM)</li> <li>❖ Wheel-Mouse included</li> <li>❖ Two USB ports (+ two @ rear)</li> <li>❖ Standard Parallel Port</li> <li>❖ Serial port</li> <li>❖ 10/100 Fast Ethernet</li> <li>❖ High 1600x1200 resolution</li> <li>❖ 32-bit color display</li> <li>❖ Stereo sound</li> <li>❖ Centrally managed</li> </ul> <p><b>Software Installed</b></p> <ul style="list-style-type: none"> <li>❖ X11 Server for X Applications</li> <li>❖ Graphics 1600x1200 at up to 32-bit colour depth</li> <li>❖ Embedded ICA Client</li> <li>❖ Embedded RDP Client</li> <li>❖ Embedded Tarantella Client</li> <li>❖ UNIX Emulation Suite</li> <li>❖ Thinprint support</li> <li>❖ PPP</li> <li>❖ REXEC</li> <li>❖ USB ( FDD, CD, ZIP, PRN, KBD and Mouse)</li> <li>❖ SMB printing</li> <li>❖ LPD printing support</li> <li>❖ Wireless LAN support</li> <li>❖ VNC</li> <li>❖ NFS / SMB (File sharing)</li> </ul>	<p><b>Ergonomics</b></p> <ul style="list-style-type: none"> <li>❖ System Stand-by</li> <li>❖ Energy saving support</li> <li>❖ Network activity indicator (rear panel)</li> </ul> <p><b>Hardware</b></p> <ul style="list-style-type: none"> <li>❖ VIA C3-800 Fanless CPU</li> <li>❖ VIA PL133 North Bridge and VT8231 South Bridge</li> <li>❖ PC133 DIMM Sockets - 1GB Max</li> </ul> <p><b>Graphics &amp; Audio</b></p> <ul style="list-style-type: none"> <li>❖ Up to 1600x1200 resolution</li> <li>❖ 32bit Color support</li> <li>❖ Up to 85Hz refresh</li> <li>❖ Integrated Trident Blade 3D Graphics</li> <li>❖ 2 Channel AC'97 Codec</li> </ul> <p><b>Networking</b></p> <ul style="list-style-type: none"> <li>❖ 10/100 Fast Ethernet</li> <li>❖ Auto speed sensing</li> </ul> <p><b>External Ports</b></p> <ul style="list-style-type: none"> <li>❖ 10/100 Fast Ethernet Autosensing</li> <li>❖ Serial port</li> <li>❖ Bi-directional parallel port</li> <li>❖ Four USB ports (1.1)</li> <li>❖ Stereo out</li> <li>❖ Line in</li> <li>❖ Mic In</li> <li>❖ VGA Display</li> <li>❖ PS/2 Keyboard</li> <li>❖ PS/2 Mouse</li> <li>❖ Power in</li> <li>❖ Power Out (for Monitor)</li> </ul>	<p><b>Internal IO</b></p> <ul style="list-style-type: none"> <li>❖ IDE Flash</li> </ul> <p><b>Power</b></p> <ul style="list-style-type: none"> <li>❖ Internal power supply</li> <li>❖ Voltage: 90-260v AC</li> <li>❖ Frequency: 50~60Hz</li> </ul> <p><b>Regulatory</b></p> <ul style="list-style-type: none"> <li>❖ CE</li> <li>❖ TUV</li> <li>❖ UL/ULC</li> <li>❖ FCC-B</li> <li>❖ CTICK</li> <li>❖ CBA</li> </ul> <p><b>Mechanical</b></p> <ul style="list-style-type: none"> <li>❖ 240 (H) x 267 (D) x 50 (W) mm</li> </ul>